



STANDARD BOAT SPECIFICATION

1. Hull and Deck

White hull and deck built in sandwich using vinilester resin, unidirectional and biaxial fibers and different density PVC cores in vacuum bagged infusion technology

2. Keel

Lifting T-keel

Stainless steel keel structure with fiberglass epoxy shell

Lead bulb

Trim Tab system

3. Steering System - JEFA

2 Carbonautica steering wheels

2 lifting rudders

4. Deck Equipment

Opening fore hatch

3 Roller mooring cleats

2 Halyard winches,

2 Primary winches in cockpit

3 winch handles

Spinlock stoppers for halyards, backstays and tacklines

Folding aluminum safety ladder

3D system for Jib barber

Antal, Ropeye, Harken Deck hardware

Bobstay (Pre-stretched Dyneema)

Magnetic marine steering compass

Main sheet traveler

Barber outhaul for Code0

5. Water System

Soft water tank capacity 55 l

Hand operated water tap in galley

Water tap in head compartment with foot pump;

Manual bilge pump in cockpit

Manual bilge pump below deck

6. Interior

Head compartment 175 cm high

Hand holds

7. Rig

Fractional Payer Carbon rig:

Mast;

Spreaders;

Boom;

Bowsprit

Stainless steel rod wire shrouds

Single line reefing system operated from cockpit

Removable Dyneema backstays/runners

Main halyard 1:2 lead aft to cockpit

J1, J3, Code0, A2 halyards

All running rig - Dyneema

Forestay/J1 Furler incl halyard swivel